

AMENDMENTS TO THE CLAIMS

Please amend Claims 1, 8, 12, 13, 15, and 17 as follows:

A3

1 1. (Currently Amended) A method for operating a network of point of presence
 2 servers [.] sharing a hostname, the method comprises:
 3 receiving a request from a user for a web page at a first web address, the
 4 first web address including the hostname;
 5 determining traffic loads of a plurality of customer web servers, each of
 6 the customer web servers storing the web page;
 7 determining a customer web server from the plurality of customer web
 8 servers that is appropriate for the request, the customer web server having a traffic load
 9 lower than traffic loads of remaining customer web servers from the plurality of customer
 10 web servers;
 11 determining an IP address of the customer web server;
 12 directing the request from the user to the customer web server; thereafter
 13 receiving a request from the user for static content on the web page at a
 14 second web address, the second web address including a ~~the~~ hostname;
 15 determining service metrics of point of presence servers in the network of
 16 point of presence servers;
 17 determining the point of presence server from the network of point of
 18 presence servers that is appropriate for the request for static content, the point of presence
 19 server having service metrics better than service metrics of remaining point of presence
 20 servers from the network of point of presence servers;
 21 retrieving the static content from the point of presence server; and
 22 providing the static content to the user.

1 2. (Original) The method of claim 1 further comprising determining
 2 load of point of presence servers in the network of point of presence servers;
 3 wherein determining the point of presence server from the network of point of
 4 presence servers that is appropriate for the request, the point of presence server having a
 5 latency and a load lower than latency or load of the remaining point of presence servers from
 6 the network of point of presence servers.

1 3. (Original) The method of claim 1 further comprising:
 2 determining whether the point of presence server includes the static content;

A3
3 determining a web server that includes the static content when the point of
4 presence server does not include the static content;
5 retrieving the static content from the web server that includes the static
6 content; and
7 storing the static content from the web server in the point of presence server.

1 4. (Original) The method of claim 3 wherein determining the web
2 server comprises:
3 determining traffic loads of the plurality of customer web servers, each of the
4 customer web servers storing the static content; and
5 determining another customer web server from the plurality of customer web
6 servers that is appropriate for the request, the another customer web server having a traffic
7 load lower than traffic loads of remaining customer web servers from the plurality of
8 customer web servers.

1 5. (Original) The method of claim 4 wherein retrieving the static
2 content from the web server comprises:
3 determining another IP address of the another customer web server; and
4 requesting the static content from the another customer web server at the
5 another IP address.

1 6. (Original) The method of claim 1 wherein the network of point of
2 presence servers comprises a domain name server.

1 7. (Original) The method of claim 1
2 wherein the request from the user for the web page is transferred from a first
3 domain name server;
4 wherein the network of point of presence servers comprises a second domain
5 name server; and
6 wherein the second domain name server determines the customer web server
7 from the plurality of customer web servers.

1 8. (Currently Amended) A method for operating a network of point
2 of presence servers comprises:
3 receiving a first request from a client DNS server to resolve a first domain
4 name, the client DNS server receiving a request from a user of a web page address that
5 includes the first domain name;

6 determining load measurements of a plurality of customer web servers, each
 7 of the customer web servers addressable by the first domain name, and each of the customer
 8 web servers configured to service the request from the user;
 9 determining a customer web server from the plurality of customer web
 10 servers, the customer web server having a traffic load measurements lower than traffic loads
 11 measurements of other customer web servers from the plurality of customer web servers;
 12 determining an IP address of the customer web server;
 13 providing the IP address of the customer web server to the client DNS server;
 14 thereafter
 15 receiving a second request from the client DNS server to resolve a second
 16 domain name, the client DNS server receiving a request from the user of a uniform resource
 17 locator that includes the second domain name;
 18 determining performance metric measurement of point of presence servers in
 19 the network of point of presence servers, each of the point of presence servers addressable by
 20 the second domain name;
 21 determining a point of presence server from the network of point of presence
 22 servers, the point of presence server having performance metrics measurements lower than
 23 performance metrics measurements of other point of presence servers from the network of
 24 point of presence servers;
 25 providing the IP address of the point of presence server to the client DNS
 26 server;
 27 retrieving data from the point of presence server in response to the uniform
 28 resource locator; and
 29 providing the data to the user.

1 9. (Original) The method of claim 8 wherein the load measurements
 2 comprise latency measurements.

1 10. (Currently Amended) The method of claim 8 wherein the
 2 performance metric measurements comprise any of: load CPU and memory
 3 measurements, HTTP response measurements, and FTP response measurements.

1 11. (Original) The method of claim 8 wherein retrieving data from the
 2 point of presence server comprises:
 3 determining whether the point of presence server includes the data;
 4 retrieving data from another customer web server from the plurality of
 5 customer web servers when the point of presence server does not include the data; and

6 storing the data within the point of presence server.

1 12. (Currently Amended) The method of claim 11 wherein retrieving
2 data from the other customer web server comprises:

3 determining the other customer web server from the plurality of customer web
4 servers, the other customer web server having a traffic load ~~measurements~~ lower than traffic
5 loads ~~measurements~~ of remaining customer web servers from the plurality of customer web
6 servers; and

7 retrieving the data from the other customer web server.

1 13. (Currently Amended) The method of claim 8 further comprising:
2 receiving a first request from a second client DNS server to resolve a third
3 domain name, the second client DNS server receiving a request from a second user of a
4 second web page address that includes the third domain name;

5 determining load measurements of a plurality of second customer web
6 servers, each of the second customer web servers addressable by the third domain name, and
7 each of the second customer web servers storing data configured to service the request from
8 the second user;

9 determining a second customer web server from the plurality of second
10 customer web servers, the second customer web server having a traffic load ~~measurements~~
11 lower than traffic loads ~~measurements~~ of other second customer web servers from the
12 plurality of second customer web servers;

13 determining an IP address of the second customer web server; and

14 providing the IP address of the second customer web server to the second
15 client DNS server.

1 14. (Original) The method of claim 13 further comprising:

2 receiving a second request from the second client DNS server to resolve the
3 second domain name, the second client DNS server receiving a request from the second user
4 of a second uniform resource locator that includes the second domain name;

5 retrieving a second set of data from the point of presence server in response to
6 the second uniform resource locator; and

7 providing the second set of data to the user.

1 15. (Currently Amended) A method for a network of point of presence
2 servers comprises:

3 receiving at a first point of presence server a first request from a first client
4 DNS server to resolve a first domain name, the first request from the first client DNS server

5 determined in response to a first uniform resource locator entered by a first user, the first
6 uniform resource locator comprising the first domain name;

7 receiving at a second point of presence server a first request from a second
8 client DNS server to resolve the first domain name, the first request from the second client
9 DNS server determined in response to the first uniform resource locator entered by a second
10 user, the first uniform resource locator comprising the first domain name;

11 determining at the first point of presence server traffic measurements of a
12 plurality of customer web servers, each of the customer web servers addressable by the first
13 domain name, and each of the customer web servers storing data associated with the first
14 uniform resource locator;

15 determining at the first point of presence server a first customer web server
16 from the plurality of customer web servers, the first customer web server having traffic[[e]]
17 ~~measurements~~ loads lower than traffic ~~loads~~ ~~measurements~~ of other customer web servers
18 from the plurality of customer web servers;

19 determining at the second point of presence server the first customer web
20 server from the plurality of customer web servers, the first customer web server having
21 traffic[[e]] ~~measurements~~ loads lower than traffic ~~loads~~ ~~measurements~~ of other customer web
22 servers from the plurality of customer web servers;

23 determining at the first point of presence server an IP address of the first
24 customer web server;

25 determining at the second point of presence server an IP address of the first
26 customer web server;

27 providing from the first point of presence server the IP address of the first
28 customer web server to the first client DNS server and to the second client DNS server;

29 providing from the second point of presence server the IP address of the first
30 customer web server to the first client DNS server and to the second client DNS server;
31 thereafter

32 receiving at the first point of presence server a second request from the first
33 client DNS server to resolve a second domain name, the second request from the first client
34 DNS server determined in response to a second uniform resource locator comprising the
35 second domain name, the second uniform resource locator from the first customer web server;

36 receiving at the second point of presence server a second request from the
37 second client DNS server to resolve the second domain name, the second request from the
38 second client DNS server determined in response to the second uniform resource locator
39 comprising the second domain name, the second uniform resource locator from the first
40 customer web server;

41 determining at the first point of presence server performance metric
 42 measurement between the first point of presence server and other point of presence servers in
 43 the network of point of presence servers, each of the point of presence servers addressable by
 44 the second domain name;

A3 45 determining at the second point of presence server performance metric
 46 measurement between the second point of presence server and other point of presence servers
 47 in the network of point of presence servers;

48 determining at the first point of presence server performance metric
 49 measurement between the second point of presence server and other point of presence servers
 50 in the network of point of presence servers;

51 determining at the first point of presence server a third point of presence
 52 server from the network of point of presence servers, the third point of presence server having
 53 performance metrics ~~measurements~~ lower than performance metrics ~~measurements~~ with
 54 regards to the first point of presence server;

55 determining at the second point of presence server a fourth point of presence
 56 server from the network of point of presence servers, the fourth point of presence server
 57 having performance metrics ~~measurements~~ lower than performance metrics ~~measurements~~
 58 with regards to the second point of presence server;

59 retrieving data from ~~[[a]]~~ the third point of presence server;

60 retrieving ~~the~~ data from the fourth point of presence server;

61 providing the data from the third point of presence server to the first user; and

62 providing the data from the fourth point of presence server to the second user.

1 16. (Original) The method of claim 15 wherein the traffic
 2 measurements comprise latency measurements.

1 17. (Currently Amended) The method of claim 15 wherein the
 2 performance metric measurements comprise any of: CPU load measurements, HTTP
 3 response measurements, and FTP response measurements.

1 18. (Original) The method of claim 15 wherein retrieving data from
 2 the third point of presence server comprises:
 3 determining whether the third point of presence server includes the data;
 4 retrieving data from another customer web server from the plurality of
 5 customer web servers when the third point of presence server does not include the data; and
 6 storing the data within the third point of presence server.

1 19. (Original) The method of claim 18 wherein retrieving data from the
2 other customer web server comprises:
3 determining the other customer web server from the plurality of customer web
4 servers, the other customer web server having load measurements lower than load measurements
A3 5 of remaining customer web servers from the plurality of customer web servers; and
6 retrieving the data from the other customer web server.

1 20. (Original) The method of claim 15 wherein the first domain name
2 and the second domain name are the same.
